



Fiber Optic Systems Technology Inc.

FT 3410 Sensor Monitor



Specifications

Dimensions (W x D x H)	11.5" x 11" x 5" (without handle) Bench-mounted height is 8.5"
Weight	5.4 kg / 11.8 lbs
Operating Environment	Designed for outdoor use. Do not expose to condensing humidity or precipitation. Operating temperature: -10°C to +45°C (14°F to 113°F)
Storage Temperature	-20°C to +65°C (-4°F to 149°F)
Number of Channels	Eight (8)
Compatible Sensor Lengths	Up to three compatible sensor lengths available per monitor
Scan Times (per channel)	30-40 seconds (full scan) 5 seconds (typical window scan)
Measurement Range	± 15 mm
Operating Accuracy	< 0.5% of full-scale (0.2% typical)
Resolution	1 µm
Display	LCD Touchscreen (3.8" diagonal)
Interface	USB 2.0 compatible
Power Requirements	AC adapter requires 100-240 V / 1.8 A, 50-60 Hz
Battery Life (approximate)	+20°C to +30°C (68°F to 86°F): +4.0 hours battery life +10°C to +40°C (50°F to 104°F): +3.5 hours battery life -10°C to +45°C (14°F to 113°F): +3.0 hours battery life

For more information please contact FOX-TEK @ (416) 665-2288

www.fox-tek.com

Specifications subject to change without notice
© 2006 Fiber Optic Systems Technology Inc. All rights reserved.